

SHANTUI

SE370LC

Crawler Excavator



Engine Model: Cummins QSL9
Gross Power: 214 kW/2100 rpm
Operating Weight: 36,800 kg
Bucket Capacity: 1.8 m³

High-Efficiency King
high return rates

SE370LC SPECIFICATIONS

ENGINE

Model	Cummins QSL9
Type	High pressure common rail, turbocharged
No. of cylinder	6
Emission	Tier 3 / Stage III
Displacement	8.9L
Power output	214kW/2100rpm

HYDRAULIC SYSTEM

Type	Variable double piston pump plus gear pump
Max. discharge flow	300×2L/min

DIGGING FORCE (ISO6015)

Bucket	254kN
Arm	174kN

BUCKET

Type	Backhoe bucket
Capacity	1.8(0.45-2.2)m ³
Width	1730mm

TRAVEL SYSTEM

Type	Axial variable plunger motor
Track roller	8X2
Carrier roller	2X2
Track shoe	49X2
Travel speed	3.0/4.9km/h
Max. Drawbar pull	315kN
Gradeability	70% (35°)

SWING SYSTEM

Swing motor type	Swash plate plunger motor
Swing speed	0-10.5r/min
Brake type	Pressure release, mechanical braking

REFILL CAPACITIES & LUBRICATIONS


Fuel tank	620L
Cooling system	35L
Engine oil	28L
Hydraulic oil tank	300L
System Capacity	420L

OPERATING WEIGHT AND GROUND PRESSURE

Shoe width	600mm
Ground pressure	68.3kPa
Operating weight	36800kg



SCOPE OF WORK (mm) (BOOM: 6470 mm ARM: 2812 mm)

A	Max. digging height	10110
B	Max. dumping height	6970
C	Max. digging depth	6995
D	Max. vertical digging depth	5460
E	Max. depth cut for 2500mm level bottom	7190
F	Max. digging distance	10840
G	Max. digging radius at ground level	10630
H	Min. swing radius of work equipment	4430



DIMENSIONS (mm)

A	Overall length	11265
B	Ground contact length (Transportation)	6890
C	Overall height (to top of boom)	3785
D	Overall width	3200
E	Overall height (to top of cab)	3290
F	Counter weight ground clearance	1340
G	Ground clearance	565
H	Tail swing radius	3520
I	Tread	4080
J	Track length	5045
K	Track gauge	2600
L	Track width	3200
M	Shoe width	600
O	Bonnet height	2910
P	Revolving frame width	3190
Q	Distance from swivel center to tail	3465



* THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.



Shantui Social

SHANTUI CONSTRUCTION MACHINERY CO., LTD.

ADD: No. 58, G327 Highway, Jining City, Shandong, CHINA

TEL: +86-537-2909369

FAX: +86-537-2311219

EMAIL: trade@shantui.com

WEB: www.shantui.com

SHANTUI

LET'S MAKE CONSTRUCTION EASIER